

Blueskin[®] Adhesive

Adhesive for Self-Adhered Membranes

Physical Properties

-Colour	Blue	-Service Temp	Minus 40°C to 70°C
-Solids by Weight	35%	-Application Temp	Minus 12°C to 40°C
-Weight	0.8 kg/l (6 lbs./gal. U.S.) (approx.)	-Flammability	Flammable
-Coverage	2 to 6 m ² /l (up to 250 ft ² /gal. U.S.) depending on porosity and texture of surface.	Wet	Burns
-Drying Time		Dry	
Initial Set	30 minutes		
Set Through	2 hours		

Description

Blueskin[®] Adhesive is a rubber based adhesive for self-adhered membranes.

Features

- Quick setting
- Aggressive tack provides increased adhesion of membrane
- Suitable for application at normal and low temperatures
- Easily applied

Uses

Used as an adhesive to increase bond strength of self-adhered membranes such as **Blueskin[®] SA, Blueskin[®] WP 200, Blueskin[®] ROOF RF 200, Blueskin PE200HT, Vapor Bloc SA** or **DuraTac** when applied to masonry, concrete, wood, gypsum board, DensGlass Gold[®] and metal surfaces.

Blueskin[®] Adhesive is the product of choice on above grade applications of self-adhered membranes where a quick setting, aggressive tack, solvent based adhesive is required.

Designed for applications above -12°C.

Limitations

Solvent in product attacks polystyrene insulation. Avoid use where solvent odours may taint food or other susceptible products..

Packaging

Blueskin[®] Adhesive is packaged in 17L and 3.5L pails.

Blueskin® Adhesive for Self-Adhered Membranes

Preparation

Surfaces must be dry and free from dust, dirt, grease, oil or other foreign matter.

Application

Apply by brush, roller or spray. Rollers should have a heavy nap of natural material such as lamb's wool. Allow Adhesive to dry for 30 minutes before applying membrane.

Coated surfaces not covered by membrane during the working day must be re-coated.

Clean Up

Use mineral spirits.

Caution

Contains extremely flammable solvents. Take suitable fire precautions. Do not allow smoking or welding in working area. Keep away from open flame or spark. Use under well ventilated conditions. Avoid prolonged breathing of vapours and repeated contact with skin. Excessive inhalation of vapours can cause dizziness. (Use respirator approved for organic vapours). Keep containers covered when not in use. Harmful if swallowed.

<>